

| Product information sheet according to VO2019/2014 annex V  |                |      |   |                |    |
|---|----------------|------|---|----------------|----|
| Supplier's name or trade mark: Schulthess Maschinen AG  |                |      |   |                |    |
| Supplier's address: Landstrasse 37, 8633 Wolfhausen - CH  |                |      |   |                |    |
| Model identifier: Superforte 740  |                |      |   |                |    |
| <b>General product parameters:</b>  |                |      |   |                |    |
| Parameter   | Value          |      | Parameter   | Value          |    |
| Rated capacity (kg)   | 9.0            |      | Dimensions in cm  | Height         | 90 |
|   |                |      |   | Width          | 63 |
|   |                |      |   | Depth          | 72 |
| EElw  | 59.6           |      | Energy efficiency class   | B              |    |
| Washing efficiency index  | 1.04           |      | Rinsing effectiveness (g/kg)  | 4.5            |    |
| Energy consumption in kWh per cycle, based on the "eco 40-60" programme. Actual energy consumption will depend on how the appliance is used.                              | 0.567          |      | Water consumption in litre per cycle, based on the "eco 40-60" programme. Actual water consumption will depend on how the appliance is used and on the hardness of the water. | 48             |    |
| Maximum temperature inside the treated textile (°C)   | Rated capacity | 41   | Remaining moisture content (%)  | Rated capacity | 44 |
|   | Half           | 30   |   | Half           | 44 |
|   | Quarter        | 23   |   | Quarter        | 44 |
| Spin speed (rpm)  | Rated capacity | 1545 | Spin-drying efficiency class  | A              |    |
|   | Half           | 1646 |   |                |    |
|   | Quarter        | 1646 |   |                |    |
| Programme duration (h:min)  | Rated capacity | 3:48 | Design type   | Free-standing  |    |
|   | Half           | 2:52 |   |                |    |
|   | Quarter        | 2:52 |   |                |    |
| Airborne acoustical noise emissions during the spinning phase (dB(A) re 1 pW)   | 75             |      | Airborne acoustical noise emission class for the pinning phase  | B              |    |
| Off-mode (W)  | 0.16           |      | Standby mode (W)  | ---            |    |
| Delay start (W) (if applicable)   | 3.02           |      | Networked standby (W) (if applicable)   | ---            |    |
| <b>Minimum duration of the guarantee offered by the supplier: 2 years</b>   |                |      |   |                |    |
| This product has been designed to release silver ions during the washing cycle  |                |      | NO  |                |    |
| <b>Additional information:</b>  |                |      |   |                |    |
| Web link to installation instructions and further information on the model (operating/set-up instructions + Quickstart): <a href="http://schulthess.ch">schulthess.ch</a> |                |      |   |                |    |
| The consumption/power values refer to the programme "eco40-60"  |                |      |   |                |    |
| Art. no. product information sheet: 540700AA  |                |      |   |                |    |