



Türumbandung mit Umbandungsset optional möglich  
 Charnières avec set de déplacement disponibles en option  
 Optional re-hinging kit to change door hinge side  
 Montaggio opposto delle cerniere possibile con il set disponibile separatamente



	Deutsch	Français	Italiano	English
①	Wasserausgang (Ø21mm) Max. Förderhöhe Pumpe: 1m Förderleistung 22l/min	Evacuation de l'eau (Ø21mm) Hauteur max. de refoulement pompe: 1m Capacité de débit 22l/min	Evacuazione dell'acqua (Ø21mm) Altezza mass. di convogliamento pompa: 1m Potenza di mandata 22l/min	Water outlet (Ø21mm) max. delivery head pump: 1m max. flow rate: 22l/min
①a	Wasserausgang (nur bei Ablaufventil)	Evacuation de l'eau (seulement pour vanne d'écoulement)	Evacuazione dell'acqua (solo per valv. di scarico)	Water outlet (Appliances with an outlet valve only)
②	Kalt- / Weich- / Regen- wasseranschluss (3/4")	Eau de pluie froid / douce (3/4")	Acqua piovana fredda / decalcificata (3/4")	cold / soft / rain water connection (3/4")
③	Kalt- oder Warm- wasseranschluss (3/4")	Raccordement eau froide ou chaude (3/4")	Alimentazione d'acqua fredda o calda (3/4")	Cold or hot water connection (3/4")
④	Elektroanschluss	Raccordement électrique	Collegamento elettrico	Electrical connection

Massblatt Waschautomat Breite 630  
 Plan d'installation machine a laver largeur 630  
 Piano d'installazione lavatrice larghezza 630  
 Dimension sheet washing machine width 630

Gez.	05.04.2016	rsc
Frg.	12.05.2017	rsc
Geä.	12.05.2017	rsc

Masstab: 1:25

**538772AC**