## SPIRIT TOPLINE DRYERS FOR APARTMENT BLOCKS

| Name of brand  | Schulthess             | Schulthess             |
|--|------------------------|------------------------|
| Model name   | Spirit topLine 830     | Spirit topLine 810     |
| Product number   | 8830.1                 | 8810.1                 |
| Max. rated capacity kg   | 8                      | 8                      |
| Category   | Condensation dryer     | Condensation dryer     |
| Appliance type   | with heat pump         | with heat pump         |
|  |                        |                        |
| Energy efficiency class from A+++ to D   | A++                    | A++                    |
| Annual energy consumption kWh  | 236                    | 236                    |
| Dryer with/without automation  | •/-                    | •/-                    |
| Energy consumption for standard cotton programme   | -7                     | -1                     |
| Full/half load kWh   | 1,99 / 1,07            | 1,99 / 1,07            |
| Standby consumption switched on/switched off state <sup>6)</sup> W   | 0,14 / 0,14            | 0.14 / 0.14            |
| Automatic switch-off period min  | 5                      | 5                      |
| Standard programme referenced by the information   | Cotton                 | Cotton                 |
| on the label and the data sheet  | cabinet dry with arrow | cabinet dry with arrow |
| Usage properties   |                        |                        |
| Estimated duration of the standard setten programme ()   | 83                     | 02                     |
| Estimated duration of the standard cotton programme <sup>1)</sup> min Programme duration full/partial load min | 108/64                 | 83<br>108 / 64         |
| Condensation efficiency category 1) from A to G  | A                      | A                      |
| Estimated condensation efficiency 1) %   | 91                     | 91                     |
| 25cmacea condendation emiciency 70   |                        |                        |
| Average condensation efficiency full/partial load %  | 90/92                  | 90/92                  |
| Noise <sup>2)</sup> dB(A) re1pW  | 66                     | 66                     |
| Model  |                        |                        |
| Built-in appliance   | •                      | •                      |
| Stand-alone unit with work surface   | •                      | •                      |
| Stand-alone unit, can be built in  | •                      | •                      |
| Door hinge 3)  | I/r/c                  | l/r/c                  |
| Appliance dimensions 4)  |                        |                        |
| Height cm  | 90                     | 90                     |
| Width cm   | 63                     | 63                     |
| Depth (including wall distance) cm   | 84                     | 84                     |
| Height for built-in installation cm  | 90,5                   | 90,5                   |
|  |                        |                        |
| Depth with door open (including wall distance) cm  | 146                    | 146                    |
| Height (adjustable) cm   | 2                      | 2                      |
| Weight when empty kg   | 88                     | 88                     |
| Electrical connection 5)   |                        |                        |
| Voltage V/Hz   | 400 2N~                | 400 2N~                |
| Connected value kW   | 3,4                    | 3,4                    |
| Fuse protection A  | 10                     | 10                     |
| Safety and customer service  |                        |                        |
| Country of origin  | CH                     | CH                     |
| Warranty 7) years  | 2                      | 2                      |
| Name and address of supplier   | Schulthess Maschinen   | AG, 8633 Wolfhausen/ZH |
| Equipment  |                        |                        |
| Heat pumps condensation system   | •                      | •                      |
| Duration of programme cotton cabinet dry before  |                        |                        |
| drying 1600 rpm spin-dry (44% residual moisture) min   | 69                     | 69                     |
| Favorites for your 6 favorite programmes   | -                      | -                      |
| Drying basket  | -                      | -                      |
| Special programme  | 9                      | -                      |
| Pollenclean programme with pollen filter   | -                      | -                      |
| Mixed / Wool finish / Express / Terry cloth / Silk   | •/•/•/-                | •/-/•/-/-              |
| Programme time display   | •                      | •                      |
| Load detection quantity  | •                      | •                      |
| Automatic door opening   | • front Ø 36 / 31      | • Front Ø 35/31        |
| Inlet opening cm   | front, Ø 36/31         | front, Ø 36/31         |
| LED drum lighting Connection cable m   | 1,65                   | 1,65                   |
| Drain hose m   | 1,9 / Ø 10 mm          | 1,9/Ø 10 mm            |
| Condensation drain with container/direct drainage with pump  | -/•                    | -/•                    |
| Maximum sequence height m  | 1                      | 1                      |
| Exhaust duct   | _                      | _                      |
|  | -                      | -                      |
|  |                        |                        |