Schulthess
TS 8 A Drying Cabinet

TS 8 A Drying Cabinet

- Efficient fan extracted drying cabinet
- Low energy consumption
- Simple to use
- 8 kg capacity
- 16 m hanging rails
- Ideal for delicate items of clothing
- Humidity sensor (HTS)
- Automatic and time-controlled programmes
- Select one of 7 languages
- Interior lighting

TS 8 A Drying Cabinet

Company or brand names		**Schulthess**
Device type		**Drying cabinet**
Type or sales description		**TS 8 A**
Product No.		9972.1
Drying cabinet		
Load	kg	8
Hanging rail	m	16
Drying capacity	g/min	62*
Drying time	min	42*
Energy consumption	kwh/kg	0.5
Noise emission	dB(A)	62

*To dry 6 kg cotton items (dry weight) with 43% residual moisture

Electrical installation		
Supply voltage	V	400
Connected load	kW	6,3
Fuse protection	AT	10
Length of power cable	mm	2500
Ventilation		
Exhaust air pipe	∅ mm	125
Extraction rate	m^3/h	230
Air intake	m^3/h	340
Cable resistance on site	max. Pa	70
Carrier/planner		
Machine width	mm	1200
Machine depth	mm	640
Machine height	mm	1870
Minimum ceiling height	min. mm	2080
Machine weight	kg	145
Carrier's weight	kg	159
Packaging volume	m^3	0,92
Options		
Security and service		
Complies with EU machine directives		2006/42/EG
Complies with CH safety regulations		Yes
Guarantee		1 year
Service by		Schulthess Maschinen AG
Name and address of the producer		AB PODAB
Country of provenance		Sweden

Schulthess Maschinen AG
Landstrasse 37, CH-8633 Wolfhausen ZH
Tel. 0844 880 880, www.schulthess.ch

Note: specifications as per 10/2018. Subject to further development.