



Model
Chrome steel



Model
Anthracite

Model Grey matt



Features

- Professional dryer (8 kg load capacity) for gentle fabric care
- Available in three model variants (exhaust air, condensation and heat pump)
- Intuitive operation with 4.3" colour display
- 22 standard programmes
- Stainless steel drum with LED lighting and a volume of 150 litres
- Robust construction for a long durability (Swiss made and designed for over 25'000 operating hours)
- Electronically time-controlled drying programmes including residual moisture measurement
- Language selection button for 23 different languages
- Door hinge right (can be changed to left on site)

Options

- Available in chrome steel (front and cover) or anthracite (complete housing)
- WLAN interface for programme and software updates
- RFID interface for card systems
- Standard machine plinth in all three colours (305 mm)
- Special machine plinth in all three colours (522 mm)

Technical data topLine TA 9340, TC 9350, TW 9360

Company or brand name	Schulthess		Schulthess	Schulthess
Type of appliance	Exhaust air dryer		Condensation dryer with heat-exchanger air	Condensation dryer with heat pump
Type or sales description	topLine TA 9340		topLine TC 9350	topLine TW 9360
Product number	7648.2U6		7649.2U6	7650.2U6
Load capacity	max. kg	11	11	11
Structural design				
Stand-alone unit with work surface	•		•	•
Standard unit for washing and drying tower	•		•	•
Door hinge ³⁾	r/l/w		r/l/w	r/l/w
Dimensions⁴⁾				
Height	cm	90	90	90
Width	cm	63	63	63
Depth including distance from wall	cm	83	84	84
Height for built-in installation	cm	90,5	90,5	90,5
Depth with door open	cm	144	146	146
Height (adjustable)	cm	2	2	2
Drying control				
By time selection ⁵⁾	•		•	•
Automatic by electronic moisture detection ⁶⁾	•		•	•
System and Equipment				
Drying technology	Air extraction system		Air condensation system	Condensation system with heat pump
Programme time display	•		•	•
Automatic door opening	•		•	•
Loading opening	cm	front, Ø 36 / 31 / 180°	front, Ø 36 / 31 / 180°	front, Ø 36 / 31 / 180°
LED drum lighting	•		•	•
Connecting cable	m	1,5	1,5	1,5
Outlet hose	m	–	2 / Ø 22 mm	2 / Ø 22 mm
Condensate drainage in container / Drainage direct	–		•	•
Exhaust air duct	Ø 100 mm, 90°-angle adapter		–	–
Maximum drain height	m	–	1	1
Exhaust hose Ø 100 mm	m	2	–	–
Power supply – Electrical connection⁷⁾				
Voltage	V	400 V 3N~ / 400 V 2N~ / 230 V 1N~	400 V 3N~ / 400 V 2N~ / 230 V 1N~	400 V 2N~
Connected values	kW	5,9 / 4,4 / 2,2	5,1 / 3,7 / 2,3	3,4
Fuse protection	AT	10 / 10 / 10	10 / 10 / 10	10
Safety and service				
Conforms to the European Machinery Directive	2006/42/EC		2006/42/EC	2006/42/EC
Country of origin	Switzerland		Switzerland	Switzerland
Guarantee ⁸⁾	1 year		1 year	1 year
Service by	Hi-Seasons			
Name and address of supplier	Schulthess Maschinen AG, CH-6330 Cham ZG			

Explanations:

– Available or yes • Not available or no

3) Door hinge: l = left, r = right, w = can be changed

Example: l/w means that the machine is delivered with the door hinge to the left, but the direction of opening can be changed.

4) The stated dimensions are minimum dimensions for the niche where the machine is built in. Further dimensions can be found in the dimension sheets.

5) Set the degree of drying according to the laundry items, as shown in the operating instructions.

6) Degree of drying is maintained automatically.

7) Information on switchover options can be found in the installation instructions, where required.

8) Outside Switzerland: 1 year

Note: State of the table details as 04.2023, subject to further developments.